



Client:

Project:

Type:

Order Code:

Quantity:

ART SSC 2 is the second generation of the powerful and flexible DMX controller designed for permanent installation. It features two universes of DMX in /out, Art-Net, sACN, PoE (Class I), and many triggering options such as TCP, UDP, OSC, and GPI (dry contact). It's astronomical time clock can trigger scenes based on specific locations, and can now automatically assign addresses with DHCP built in.

SPECIFICATIONS


DMX Output	1024 channels, 2 universes
DMX Input	1024 channels, 2 universes
Alternate Control Protocols	Art-Net, sACN
Trigger Protocols	TCP, UDP, OSC, GPI (dry contact x4), MIDI, MSC, MMC
Sync Protocols	SMPTE, MTC, Art-Net timecode
Operating Voltage	9-24VDC, 500mA (power adapter included, 100-240VAC input)
Power Over Ethernet	Included, Class I
IP Settings	via DHCP or static
Mounting	DIN rail or Desktop (un-mounted)
Anti-Theft	Compatible with Kensington lock system (not included)
Finish	Black
Material	Polycarbonate
Ambient Operating Temperature	14° F to 122° F (-10° C to 50° C)
IP Rating	IP20, dry location
IK Rating	IK06, protection against 1 joule impact
Fixture Connectors	5 Pin XLR (DMX), RJ45 (Ethernet, Art-net, sACN), terminal block (GPI x 4)
Warranty	2 Years, limited
Weight	0.8 lbs (363kg)
Dimensions	L: 6.99" W: 3.94" D: 1.5" (170 x 100 x 380mm)
Certifications	CE

ORDER CODES

ART002: Art SSC 2 DMX Controller

INCLUDED COMPONENTS

Power Supplies



ART002-PSU

Power Supply for ART SSC 2
100-240VAC, 1A, 12VDC, 12W
cULus, FCC, CE approved

DIMENSIONS

