



Client:

Project:

Type:

Order Code:

Quantity:

AL Driver 1 is a single channel PWM dimming driver for low voltage LED products. It can take a DC input from 6-24VDC and control protocols are DMX or 0-10V (sink and source). It can control up to 5A of single color LED product, and a manual dimming level can be set in instances where external control is not desired.

SPECIFICATIONS

| | |
|-------------------------------|---|
| Power Input | 6-24VDC, 5A maximum |
| Control Input | DMX, 0-10V (sink and source) |
| Output | Single channel PWM dimming, 0-100% |
| Optional Control | Manual dimming level selection via dip switch |
| Mounting | 4 x 0.15" (4mm) mounting holes |
| Finish | Black |
| Material | Polycarbonate |
| Ambient Operating Temperature | 14° F to 122° F (-10° C to 50° C) |
| IP Rating | IP20, dry location |
| IK Rating | IK06, protection against 1 joule impact |
| Fixture Connectors | Removable multi-pin terminal blocks |
| Warranty | 5 Years, limited |
| Weight | 0.1 lbs (45g) |
| Dimensions | W: 2.32" L: 1.18" H: 0.78" / W: 59mm L: 30mm H: 20mm |
| Certifications |   |

ORDER CODE

ALD001

DMX In / PWM Out

