



Client:

Project:

Type:

Order Code:

Quantity:

**AL Fade 6 Pro** is simple, fader based wall-mount DMX controller designed for single color or multi-color LED lighting products. It features a six channel DMX output, six user programmable presets (static color or moving sequence), and a master dimmer function. An IR remote control is included for wireless control up to 30'.

## SPECIFICATIONS

DMX Output	6 channels
DMX Input	6 channels, overrides dimmer levels for programming
Interface	Dimmable faders and preset buttons
Multiple Locations	Not available for AL Fade 6 Pro
Adjustable Start Address	Available via back panel dip switches
Operating Voltage	12-24VDC, 500mA (power adapter included - 6W, 12VDC, 100-240VAC input)
Mounting	Single gang electrical box (not included)
Finish	White
Material	Aluminum housing, glass panel
Ambient Operating Temperature	32° F to 104° F (0° C to 40° C)
IP Rating	IP20, dry location
Fixture Connectors	Screw terminal block, direct hardwire
Warranty	2 Years, limited
Weight	0.3 lbs (140g)
Dimensions	<b>L:</b> 4.72" <b>W:</b> 2.99" <b>D:</b> 0.6" (120 x 76 x 15.3mm)
Certifications	CE

## ORDER CODES

**ALF6PU:** AL Fade 6 Pro (North American Version)

**ALF6PE:** AL Fade 6 Pro (European Version)

## INCLUDED COMPONENTS

### Power Supplies



#### **APS-6-12**

*Power Supply for AL Fade 6 Pro*  
100-240VAC, 500mA, 12VDC, 6W  
cULus component, CE approved

## DIMENSIONS

