Ai Cove™





Client:	
Project:	
Type:	
Order Code:	
Quantity:	

Ai Cove is a unique, dim to warm interior cove fixture.

Available in 1' and 4' sections, it features Acclaim's proprietary **Ai Dim** (Acclaim Intelligent Dimming) technology. Ai Dim is a combination of a finely tuned dimming curve and a specific grouping of LEDs which results in a near perfect representation of incandescent dimming.

Specifications


Color	3000K - 1800K
Available Lengths	1' & 4'
Beam Angle	120°
Max Fixtures In Series	50' (15.2m) @ 120V, 100' (30.4m) @ 240V+
Photometrics	500 lumens per foot, 93 CRI
Control	TRIAC (forward phase), ELV (reverse phase), 0-10V, DMX (0-10V & DMX require external UDM)
Mounting	30° Swivel Mount Included, 90° Swivel Mount Optional
Power Consumption	13.5W (1'), 53W (4')
Operating Voltage	120VAC, 240VAC, or 277VAC
Lumen Maintenance	L70 @ 150,000 Hours 25° C
Finish	White standard, black, gray, or custom optional
Housing Material	Aluminum body, Polycarbonate Lens
Ambient Operating Temperature	-4° F to 113° F (-20° C to 45° C)
IP Rating	IP20, Dry Location
Fixture Connectors	Attached 3 Conductor AC Lead, Includes end-to-end link cable
Warranty	5 Years
Weight	1': 0.65 lbs (0.29 kg), 4': 2.75 lbs (1.25 kg)
Dimensions	L: 12" / 48" (L: 304mm / 1220mm, W: 1.6" (40mm), H: 1.6" (40mm)
Certifications	. C€

Ai Cove™




Order Codes

* Indicates Special Order



Dimensions

*Standard 30° swivel bracket shown. 90° optional bracket raises height to 2.2" (56mm)



Ai Cove™



Related Components

Cables

AICFC10 Ai Cove 10' Feed Cable + End Cap

AICLC1 Ai Cove 1' Link Cable

AICLC5 Ai Cove 5' Link Cable

AICLC10 Ai Cove 10' Link Cable

Mounting Accessories



AIC90

90° Bracket for Ai Cove (Single)

Control Accessories



UDM


Universal Dimming Module

Inputs: 0-10V (Sink or Source), DMX

Outputs: 0-10V (Sink or Source), DMX, IGBT (Digital Line Voltage)

Wiring

ELV/TRIAC



0-10V / DMX

